



Università degli Studi di Pisa
Laurea Specialistica in Informatica
Laurea Specialistica in Informatica e Networking

Advanced Programming
Final Term Paper

Copyright © 2014, Giuseppe Attardi.

Only copies for strictly personal use, in order to prepare the submission, are allowed. Any other use is forbidden and will be persecuted.

Start Date: 11/03/2014

Submission deadline: 31/03/2014 (send a single PDF file to attardi@di.unipi.it)

Rules:

The paper must be produced personally by the student, signed implicitly via his mail address.

You are allowed to discuss with others the general lines of the problems, provided that each student eventually formulates his own solution. Each student is expected to understand and to be able to explain his solution.

You are allowed to consult documentation from any source, provided that references are mentioned.

It is not considered acceptable:

- **to consult or setup an online forum, to request help of consultants in producing the paper**
- to develop code or pseudo-code with others
- to use code written by others
- to let others use someone's code
- to show or to examine the work of other students.

Violation of these rules will result in the cancellation of the exam and a report to the Presidente del Consiglio di Corso di Studio.

For the programming exercises you can choose a programming language among C++, C# and Java.

The paper must:

1. be in a single PDF file, formatted readably (**font size ≥ 10 pt** with suitable margins, single column), of **no more than 10 numbered pages**, including code: for each extra page one point will be subtracted from the score.
2. include the student name
3. provide the solution and the code for each exercise separately, referring to the code of other exercises if necessary. **Do not include in an exercise code only needed for a later exercise.**
4. cite references to literature or Web pages from where information was taken.

Introduction

We will develop a simple Template Engine. A template is built from a string which may contain the following notations:

<code><%par></code>	refers to a template parameter of name <code>par</code>
<code><%par.attr></code>	refers to attribute <code>attr</code> of parameter <code>par</code>
<code><%if(test)>body</%if></code>	includes <code>body</code> if <code>test</code> is true
<code><%repeat(par)>body</%repeat></code>	repeats <code>body</code> for all values in the collection <code>par</code> . Within <code>body</code> the special parameter <code>it</code> will refer to the current value of the iterator on the collection.

For example, using the following template:

```
<table>
  <%repeat (popes)><tr><td><%it.first></td><td><%it.last></td></tr></%repeat>
</table>
```

a program like this will generate an HTML table:

```
public class Pope {
    public Pope(string first, string last) {
        this.first = first;
        this.last = last;
    }
    public string first;
    public string last;
}

Pope[] list = new Pope[] {
    new Pope("Paolo", "Sesto"),
    new Pope("Francesco", "Primo")
};
Template tableGen = Template.parse("<table> ... </table>");
Environment env = new Environment();
env.bind("popes", list);
String table = tableGen.gen(env);
```

The value assigned to table will be:

```
<table>
  <tr><td>Paolo</td><td>Sesto</td></tr>
  <tr><td>Francesco</td><td>Primo</td></tr>
</table>
```

Exercise 1

Implement the class `Template` and suitable subclasses of `Template`, providing a polymorphic method `gen()`, as well as class `Environment`.

Exercise 2

Add the possibility of defining parametric templates, as in this example with two parameters:

```
<%lambda(x, y)>body</%lambda>    defines a template with parameters x and y with body
                                body
<%templ(x, y)>                  includes the expansion of template templ with parameters x and y
```

For example, defining:

```
<%lambda(user)><tr><td><%user.first></td><td><%user.last></td></tr></%lambda>
```

The previous example could be written as:

```
Template tableGen =
    Template.parse("<table><%repeat (popes)><%row(it)></table>");
Template rowGen = Template.parse("<%lambda(user)> ... </%lambda>");
Environment env = new Environment();
env.bind("popes", list);
env.bind("row", rowGen);
string table = tableGen.gen(env);
```

Exercise 3

Provide an example of use of construct `<%if>` and show the output produced by the generator.

Exercise 5

Illustrate the typical technique for implementing parametric polymorphism. In which of the languages C++, Java and C#, polymorphic methods can be virtual?